

Excellence in automation
for a wide range of
market segments and applications



NOVUS
We Measure, We Control, We Record

Products and solutions for automation present in over 60 countries



About NOVUS

For the last 40 years, **NOVUS** has developed and manufactured innovative and reliable products for data acquisition, temperature control, process control, signal conditioning and transmission of field variables. All devices comply with worldwide quality requirements, thus providing solutions that exceed customers' expectations.

NOVUS is present in over 60 countries through a network of more than 300 distributors in addition to its own sales offices in South America, North America and Europe.

In 2018 **NOVUS** moved its headquarters to Canoas, southern Brazil. The new plant was designed for **NOVUS** specific needs, has three thousand square meters dedicated to the factory and, overall, surpasses five thousand square meters of built area. Its bespoke structure ensures the possibility to expand production capability four times.

All **NOVUS** products are produced in real-time reconfigurable and autonomous manufacturing cells, following Industry 4.0 concepts.

Moving a highly skilled staff to larger and modern facilities opened the path to productivity improvements aligned with **NOVUS** strategic planning. With an advanced production infrastructure and fully equipped research laboratories, the company is now able to achieve higher throughput in a larger portfolio of valued added products, therefore increasing national and international market shares.

Currently, half of what is produced by **NOVUS** is destined for the international market. Export demand keeps growing due to a worldwide recognition of the quality and value of **NOVUS** products.

Certifications and Approvals



Summary Business Units



Data Acquisition and Communication

Data acquisition systems, I/O modules, wireless connectivity and gateways.

4



Sensing, Conditioning and Transmitters

Signal conditioners, temperature, relative humidity and pressure transmitters.

9



Process Control and Indication

Process controllers, temperature controllers, process indicators, electronic thermostats and HMIs.

18



Software Interface

Computer software and smartphone applications (for device configuration, data download and data acquisition), SCADA software, and cloud based platforms.

5, 11 e 21



Metrology Services

Metrology services for temperature, relative humidity, pressure and electrical parameters.

27

Data Acquisition

Wireless Multichannel Data Loggers - LogBox Connect

LogBox Connect provides data acquisition and connectivity for any type of application. With all its wireless options, it is the gateway to the connected IoT world.

Bluetooth Data Logger

- Suitable for **battery operated** applications
- Configuration and downloading data via USB (NXperience) or **Bluetooth (NXperience Mobile)**
- Memory capacity up to **140,000 logs**
- Powered by 4 AA alkaline batteries or external DC power supply
- Input channels - 3 analogs and 1 digital

APPLICATIONS



Laboratory



Cold Chain



Data Centers



LogBox BLE

Wi-Fi Data Logger

- Suitable for distributed environments with existing **Wi-Fi infrastructure**
- Configuration and downloading data via USB or Wi-Fi - Modbus TCP (**NXperience**)
- **E-mail alarm** notification
- **MQTT** communication protocol - Cloud based platforms, **NOVUS Cloud** and **IoT Brokers**
- Input channels - 3 analogs and 1 digital

APPLICATIONS



Distribution Centers



Cold Chain



Commercial Refrigeration



LogBox Wi-Fi

GSM Data Logger

- Suitable for mobile applications in **long distance locations**
- Configuration and data download via USB or **3G (NXperience)**
- **SMS alarm** notification
- Built-in rechargeable **backup battery** with more than **8 hours** autonomy
- Easy integration with **NOVUS Cloud**
- Data communication via 3G network through NXperience and **SCADA softwares**

APPLICATIONS



Utility Services



Transportation of Temperature Sensitive Products



Agricultural Greenhouses



LogBox 3G

Software Interface

Configuration and Download Software

NXperience makes it possible to adjust the device parameters and functionalities, allowing secure data downloading.

Download and complete analysis, graphical viewing, mathematical formulas, and reporting.

With extensive connectivity, powerful data analysis and visualization capabilities, users can access **different NOVUS devices** via USB, Modbus RS485, Ethernet/Wi-Fi (Modbus TCP/IP) and cloud data from **NOVUS Cloud**.



NXperience



Flexibility of Configuration



Device Diagnostics




Analytical Reports

Validation software for Configuration and Download

NXperience Trust has GMP (Good Manufacturing Practice) compliance, meeting with the technical requirements of **FDA 21 CFR Part 11** for validation of computer systems. The user has an electronic record of encrypted data, a strong authentication mechanism with password validity, and an application event log for traceability and audit trail. Protocols and execution of validation are optional and offered separately, to complement the solution.



HARDKEY
More reliability in the data record



NXperience Trust



Inviolable Information



Data Security



Complies with 21 CFR Part 11

Configuration and Download Mobile App

NXperience Mobile is a smartphone application (Android and iOS) for configuring and downloading data wirelessly from **LogBox BLE** and **LogBox Wi-Fi** devices. Besides, it is possible to run device diagnostics and export registered data.



Setting Parameters



Data Export



Alarm Notification



NXperience Mobile

Data Acquisition

Micro Data Logger for Temperature and Humidity

LogBox-RHT-LCD is a data logger with integrated sensors for temperature and humidity. It uses high-quality sensor, for accurate and reliable transportation applications, storage of perishables, audit processes, among others.

You can quickly check the minimum and maximum values that occurred during acquisitions on **LogBox-RHT-LCD** display. This logger has a **32,000 registers** memory, 16,000 for each channel. The estimated **life battery** life is up to **200 days** with one weekly download and 5 minutes measuring interval.

NXperience software enables configuring, collecting, plotting, analysis, and export records.



LogBox-RHT-LCD

Rugged Data Loggers



	LogBox AA	LogBox DA	LogBox RHT
Input Signals	2 analog Inputs	1 digital Input 1 analog Input	Temperature and relative humidity sensors
Analog Signal Type	Thermocouples J, K, T, N, R, S, and B, Pt100, 0-50 mV, 0-10 V, 0-20 mA, 4-20 mA	(0-50 mV, 0-10 V, 0-20 mA, 4-20 mA)	-
Digital Outputs	1 electronic switch		-
Resolution	14 bits		Temperature 14 bits humidity 12 bits
Memory Capacity	64000 records		64000 records (32000 temperature and 32000 humidity)
Logging Interval	1 sec to 18 h		
Logging Mode	Instantaneous, average, minimum or maximum		
Logging Trigger	Date/time, start button or digital input	Date/time	Date/time, start button or setpoint
Alarms	2 alarms (one per channel) minimum and maximum values		
Communication Interface	Infrared through IR Link-3		
Configuration Software	NXperience (Window based)		
Power Supply	3.6 V replaceable lithium battery (½ AA)		
Battery Life	Typically 1 year		
Housing Protection	IP65		IP40



Industrial Multichannel Data Logger - FieldLogger

FieldLogger is a high-performance instrument for reading and recording variables. It has high inputs/outputs density and several options for displaying, logging and processing information. It can also be used as an analog + digital I/O expansion for PLCs in monitoring and control applications.



I/Os

- 8 Universal analog inputs
 - Thermocouples (J, K, T, N, E, R, S, and B), 0-5V, 0-10V, mV, mA, Pt100, and Pt1000
 - 128 virtual channels (refer to Mathematical Functions)
 - Sampling rate up of to 1000 readings/second (24-bit A-D conversion)
- 2 Relay outputs
- 8 Digital I/Os individually configurable as input or output



RECORDING

- Internal memory of up to 512,000 recordings
- Memory extension with SD or SDHC card
- Records up to 100 channels (local, remote or virtual variables)
- Recording rate of 1000 logs/second (max)
- Data download through configuration software (USB device, RS485, Ethernet or USB drive)




HMI

- 2.4" color QVGA screen and 96 x 48 mm format
- Screen menu with current channel value, history chart, and status information
- Allows to view and configure parameters
- Local or remote installation with RS485 communication



Optional HMI with color QVGA display



FieldLogger



COMMUNICATION INTERFACES

- RS485 "Master" for reading from up to 64 remote channels (Modbus protocol)
- RS485 "Slave" for communicating with SCADA software or Host
- USB "Device" port for instrument configuration and data download
- USB "Host" port for downloading recorded data into USB drive)
- Ethernet (10/100 Mbps) – Optional
 - Protocols DHCP, HTTP, FTP, SNMP, SMTP Client, and
- Modbus TCP
 - Custom webpage server in XML format
 - Operates as a gateway between a Modbus TCP network and a Modbus RTU network



MATHEMATICAL FUNCTIONS

- Supports up to 128 virtual channels
- Each virtual channel is a mathematical or logical operation performed over any input channel
- The result of one virtual channel can be used as input to another, which allows one to create complex formulas



ALARMS

- Up to 32 configurable alarms (with local, remote or virtual channels)
- The occurrence of an alarm allows:
 - Relay activation
 - Digital outputs activation
 - Sending emails to multiple recipients
 - Sending SNMP traps
 - Start and stop logging

I/O Modules

Ethernet I/O Module

- Mixed I/Os (analog and digital)
- Ethernet with Modbus TCP/IP protocol
- RS485 with Modbus RTU protocol
- Configurable via USB
- Advanced I/O functions

DigiRail Connect is a versatile DIN rail I/O module with Ethernet interface which can be easily integrated to any automation system. With a flexible mix of industry-standard inputs and outputs, it performs field analog and digital signal handling with outstanding accuracy. Specially designed to comply with international electromagnetic compatibility standards, it ensures robustness and reliability in the most demanding industrial applications.



APPLICATIONS



Industry



Energy



Steel Industry



Distribution Center



Programmable I/O Module

- Mixed I/Os (analog and digital)
- Rugged and reliable for industrial applications
- RS485 interface
- High-Level Programming with Arduino IDE

DigiRail NXprog is a programmable I/O module compatible with Arduino integrated development environment (IDE). With a mix of both analog and digital I/Os, **DigiRail NXprog** can be used as a controller in custom applications for machine or process automation. Flexible user programmability allows access to the local I/Os and the communication interface. The device can run complex algorithms and can connect with other devices via Modbus RTU protocol. **DigiRail NXprog** can run Arduino library codes or custom ones, providing great versatility in a wide range of applications.



APPLICATIONS



General Automation



Food and Beverage



Plastics and Packaging



Water and Wastewater



Communication

I/O Module for OEE/MES

DigiRail OEE is an I/O module designed for OEE (Overall Equipment Effectiveness) and MES (Manufacturing Execution System) industrial systems. It is the ideal tool to read the sensors that monitor the operation of machines, devices, or processes. Among its many applications, it allows to count operation time and downtime, the amount of approved and rejected parts, signal the need for preventive or corrective maintenance.

Provided with Modbus TCP and secure MQTT protocol, **DigiRail OEE** transmits data natively to Google Cloud, Microsoft Azure, Amazon AWS, **NOVUS Cloud**, or any other compatible IoT cloud platform.

Communication Interfaces	Ethernet or Wi-Fi, RS485 and USB
Inputs and Outputs	6 Digital Inputs, 2 Analog Inputs and 2 Digital Outputs
Digital Signals	NPN, PNP, and dry contact
Analog Signals	0-5 V, 0-10 V, 0-20 mA and 4-20 mA
Buffer Capacity	1800 logs with all inputs enabled 7000 logs with 1 input enabled
Clock Sync	Synchronize the clock through an NTP (Network Time Protocol) server
Maximum Pulse Count Frequency (square wave)	Dry contact: 10 Hz; PNP: 3 kHz; NPN: 3 kHz



Modbus IO Modules

DigiRail signal conditioning modules can easily integrate different analog or digital signals into PLCs or supervisory systems in a cost-effective way being the right choice for input and output expansion with great flexibility.

- Communication and status LED indicators
- Universal and configurable inputs and outputs
- Configuration and calibration can be performed with the free **DigiConfig** software



DigiRail 2A, 2R e 4C

DigiRail 2A

Two universal analog inputs

- Analog inputs: type J, K, T, E, N, R, S and B T/Cs, Pt100, mV, V, mA
- Resolution: 17 bits
- Isolation: 1000 Vac between inputs and power or communication port

DigiRail 4C

Four digital I/Os

- Fast inputs allow up to 1000 Hz digital signals
- Resolution: 32-bit counting
- Isolation: 1000 Vdc between input

DigiRail 2R

Two relay outputs

- 8 A / 250 Vac SPDT relay, resistive load
- Configurable activation time
- Isolation: 2000 Vac between power and communication

Electrical Parameters Transmitter

DigiRail-VA is a cost effective electrical parameters signal conditioner and transmitter specifically designed for single phase AC power analysis and measurement applications.

- Measures voltage, current, active power, apparent power, reactive power, frequency, and power factor
- Retransmits the measured variables in both analog and digital (RS485 Modbus) ways
- Features a USB interface for configuration and reading
- Easy-to-use DigiConfig configuration software (free of charge)



DigiRail VA

Communication


Wireless Modbus Gateway

AirGate Modbus is a multifunctional device that can be used as a wireless repeater, Modbus master multiplexer, Modbus network wireless segment or as an RS485 USB converter.

- Wireless branches for any wired RS485 network node
- Four operation modes
- Automatic configuration of a wireless tree topology network
- Connects devices up to 1000 meters apart
- Easy-to-use configuration software



AirGate Modbus



USB to RS485 Converter

Fast and reliable solution for interfacing between PCs and RS485 or RS422 industrial communication buses.

- **Plug and Play** USB Interface
- Compatible with any serial communication application
- **Compact** and easy to use in the field
- 1500 Vdc **galvanic isolation** between the USB port and RS485/RS422



USB i485

Profibus to Modbus Gateway

DigiGate Profibus is a cost-effective gateway for communication between Profibus and Modbus RTU networks. The gateway takes care of all protocols specificities to forward Profibus DP commands to devices connected in a Modbus network.

- LED indicators for communication status
- Reliable interconnection between a Profibus and a Modbus network
- Profibus network acts as the master to Modbus devices
- Easy configuration via **DigiConfig** for Windows®



DigiGate Profibus


Software Interface

SCADA – Supervisory Software

SuperView is an industrial process control and supervision software (SCADA) that presents a visual development model to the user for building applications. Besides the communication with Modbus RTU and Modbus TCP devices, it is also possible to use **SuperView** workstations as Client and Server to manage geographically distributed processes on TCP/IP networks.




SuperView



SuperView Mobile

Dashboard and IoT Cloud Platform

NOVUS Cloud is a platform focused on Internet of Things solution that expands the horizons of data viewing. Combined with **NOVUS** devices, this platform receives, stores, analyzes and displays on dashboards measurements of temperature, humidity, pressure, geolocation or any other variable of interest. Data access via the Internet is particularly necessary for several market segments, such as logistics, health, building, energy, sanitation, and agribusiness areas.




Data Acquisition Software

FieldChart is a data acquisition software, which allows the monitoring and recording of data from **NOVUS** devices in an easy, fast and intuitive way.

Suitable for use in any process, **FieldChart** also allows the configuration of alarms, as well as their acknowledgment, and the automatic saving of real-time data in a file.

The software is offered in two versions: **FieldChart-Lite** (limited to 8 monitoring channels) and **FieldChart-64C** (allows up to 64 monitoring channels). **FieldChart** makes the recorded data available in graph format or as a variable list.



FieldChart

Relative Humidity and Temperature Transmitters

Wireless Relative Humidity and Temperature Transmitter

RHT Air is a wireless relative humidity and temperature transmitter which operates over long distances and allows configuration and parameters reading over a wireless network within 500 m distance. It has a long operating battery life combined with the convenience of a wireless sensor that avoids electrical noise susceptibility ensuring a robust and secure solution. Operation without cables or wires simplifies installation and relocation of devices. **RHT Air** operates on its own wireless network and works independently from the company's IT infrastructure.

- Relative humidity and temperature measurement over long distances
- Independent industrial wireless network
- Long operating battery life
- Easy network scalability
- Noise immunity



RHT Air

Wall mounting



	RHT WM	RHT WM 485 LCD	RHT XS	RHT P10	RHT Air
Input Type	Integrated RHT probe		Extended RHT probe (3 m cable)	Extended RHT probe (flange mounting) (3 m cable)	Integrated RHT probe
Measurement Range	Temperature: -10 to 65 °C (14 to 149 °F) Humidity: 0 to 95% RH	Temperature: -40 to 70 °C (-40 to 150 °F) Humidity: 0 to 95% RH	Temperature: -40 to 120 °C (-40 to 248 °F) Humidity: 0 to 100% RH		Temperature: -10 to 70 °C (14 to 158 °F) Humidity: 0 to 95% RH
Accuracy	Temperature: ± 2 °C (3.6 °F) RH: ± 3 % (20 - 80% RH) and ± 5 % (0 - 100% RH)				
Analog Output Type	4-20 mA	-	4-20 m		-
Advanced Functions	Dew point retransmission	Dew point indication	Dew point retransmission		Battery level dew point indication
Communication	Through TxConfig adapter	RS485 Modbus RTU	Through TxConfig adapter		USB mini-B type NOVUS Air (IEEE 802.15.4)
Approvals	CE				Anatel (0172-13-7089) FCC and CE
Operating Conditions (Housing)	-10 to 65 °C (14 to 149 °F) 0 to 95% RH	-40 to 70 °C (-40 to 150 °F) 0 to 95% RH	-10 to 65 °C (14 to 149 °F) 0 to 95% RH		-10 to 70 °C (14 to 158 °F) 0 to 95% RH
Power Supply	12-30 Vdc	12-30 Vdc	12-30 Vdc		12-30 Vdc or Replaceable 3.6 V Lithium battery
Ingress Protection	Housing: IP65 Probe: IP40				IP40



High Accuracy Relative Humidity and Temperature Transmitter

RHT Climate relative humidity and temperature transmitter provides highly accurate and stable measurements and transmits both signals via two independent analog outputs and the RS485 Modbus RTU communication. The **RHT Climate** is fully USB configurable through its free **NXperience** software which also performs diagnostics and input/output simulation, installation and commissioning tasks.

RHT Climate is available with or without LCD display for duct or wall mounting with different probe lengths.

- High accuracy measurement
- Large display with backlight
- Configurable analog outputs
- Configuration via USB or front keys
- Alarm outputs and buzzer



RHT Climate

Duct Mounting




RHT Climate WM	RHT Climate WM LCD	RHT DM	RHT DM 485 LCD	RHT Climate DM	RHT Climate DM LCD
Integrated RHT probe		Integrated RHT probe (options: 150, 250, and 400 mm)			
Temperature: -40 to 60 °C (-40 to 140 °F) Humidity: 0 to 100% RH		Temperature: -40 to 120 °C (-40 to 248 °F) Humidity: 0 to 100% RH	Temperature: -40 to 100 °C (-40 to 212 °F) Humidity: 0 to 100% RH		
Temperature: ± 0.2 K (0 to 60 °C) (32 to 140 °F); Humidity: ± 1.8 % RH and 23 °C (0 - 90 % RH)		Temperature: ± 2 °C (3.6 °F) RH: ± 3 % (20 - 80% RH) and ± 5 % (0 - 100% RH)	Temperature: ± 2 °C (3.6 °F) RH: ± 3 % (20 - 80% RH) and ± 5 % (0 - 100% RH)	Temperature: ± 0.2 K (0 to 60 °C) (32 to 140°F); Humidity: ± 1,8 % RH and 23 °C (0 - 90 % RH)	
4-20 mA or 0-10 V (10-0 V)		4-20 mA	-	4-20 mA or 0-10 V (10-0 V)	
Psychrometric properties, alarm buzzer, 2 digital outputs, maximum and minimum values, simulation of inputs, simulation of outputs, custom calibration and front keys (LCD version only)		Dew point retransmission	Dew point indication	Psychrometric properties, alarm buzzer, 2 digital outputs, maximum and minimum values, simulation of inputs, simulation of outputs, custom calibration and front keys (LCD version only)	
USB Micro-B Type and RS485 Modbus RTU		Through the TxConfig adapter	RS485 Modbus RTU	USB Micro-B Type and RS485 Modbus RTU	
CE		CE			
-40 to 60 °C (-40 to 140 °F) 0 to 95% RH		-10 to 65 °C (14 to 149 °F) 0 to 95% RH	-40 to 70 °C (-40 to 158 °F) 0 to 95% RH	-40 to 60 °C (-40 to 140 °F) 0 to 95% RH	
12-30 Vdc		12-30 Vdc			
Housing: IP65 Probe: IP30 or IP40		Housing: IP65 Probe: IP40		Housing: IP65 Probe: IP30 or IP40	

Temperature Transmitters

Head Mounted Temperature Transmitter

TxBLOCK-USB is an excellent and powerful high-accuracy loop-powered head mounted temperature transmitter. It accepts several types of sensors – thermocouples, Pt100, Pt1000, NTC and 0-50 mV signal – all-in-one model, with linearized 4-20 mA output and configurable measurement range.

The innovative built-in USB port allows configuration, easy commissioning and fine tuning on periodic calibration reviews.



TxBLOCK-USB

Sensor Probe Mounting

Wall Mounting

Head Mounting



	TxMini M12	TxMini M12 485	TxMini DIN43650	TEMP WM 4-20mA	TxBLOCK USB RTD
Type	Pt100 / Pt1000 sensor programmable range	Pt100 sensor programmable range	Pt100 / Pt1000 sensor programmable range	Integrated probe	Pt100 sensor programmable range
Accuracy	0.2% of span			0.9% of span	0.2 % of span
Input Type	Pt100 and Pt1000	Pt100	Pt100 and Pt1000	Integrated temperature sensor	Pt100
Output Type	4-20 mA 20-4 mA			4-20 mA 20-4 mA	4-20 mA 20-4 mA
Range	-200 to 650°C (-328 to 1202 °F)	-200 to 600°C (-328 to 1112 °F)	-200 to 650°C (-328 to 1202 °F)	-50 to 120°C (-58 to 248°F)	See manual
Configuration Interface	TxConfig M12 interface		TxConfig DIN43650 interface	TxConfig USB interface	USB Micro-B Type
Software	TxConfig II	DigiConfig	TxConfig II	TxConfig	TxConfig II
Operating Conditions	-40 to 85 °C (-40 to 185 °F) 0 to 90% RH			-20 to 65 °C (-4 to 149 °F) 0 to 90% UR	-40 to 85 °C (-40 to 185 °F) 0 to 90% RH
Power Supply	Loop powered 4-20 mA (8 - 35 Vdc)	7 - 40 Vdc	Loop powered 4-20 mA (8 - 35 Vdc)	12 - 30 Vdc	Loop powered 4-20 mA (12 - 35 Vdc)
Dimensions	51.2 mm x 20 mm (2.01 in x 0.79 in)	59.7 mm x 20 mm (2.35 in x 0.79 in)	28.5 mm x 28.5 mm (1.12 in x 1.12 in)	70 mm x 60 mm (2.75 in x 2.36 in)	34 mm x 18 mm (1.34 in x 0.71 in)
Housing	Polyamide		ABS UL94-HB	Polycarbonate	ABS UL94-HB
Format/ Mounting	M12 Connector Thread PG9 to Probe		DIN43650 Connector M24x2 Screw	Wall	Head

HART® Temperature Transmitters

The **TxIsoRail-HRT** temperature transmitter combines the proven quality of HART® certification with the robustness of **NOVUS** devices. It is compatible with HART® certified devices and has electrical isolation between input and output, supporting voltage surges up to 1.5 kVrms.

Using a worldwide known protocol, with over 40 million field instruments supporting HART® technology, **NOVUS TxIsoRail-HRT** temperature transmitter enables the use of standard HART® configuration and supervision software that provides users with great flexibility in remote configuration and calibration capability through the two-wire 4-20 mA current loop without having to remove it from the plant.

TxIsoRail HRT and **TxIsoBlock HRT**, the **NOVUS HART®** temperature transmitters, are fully compatible with HART® certified devices from worldwide market. Full configuration can be done only with two-wire 4-20 mA current loop, providing more features for device configuration and monitoring and this is the big spotlight of the HART® devices. When a configuration change is needed, for example, remote interaction can be done with the device without removing it from the installation place.



TxIsoBlock HRT



TxConfig HRT Configurator



TxIsoRail HRT



DIN Rail Mounting



TxBlock-USB	TxIsoPack	TxIsoBlock HRT	TxRail USB	TxIsoRail	TxIsoRail HRT
Universal programmable	Universal isolated programmable	Universal isolated HART programmable	Universal programmable	Universal isolated programmable	Universal isolated HART programmable
Pt100 / mV: 0.2 % span T/C: 0.15% range ±1 °C (± 1.8 °F) NTC: 0.7% span	Pt100 / mV: 0.2 % span T/C: 0.7% span	Pt100 / mV: 0.15 % span T/C: 0.15 % span ±1 °C (± 1.8 °F) NTC: 0.45% span	Pt100 / mV: 0.2 % span T/C: 0.15% span ±1 °C (± 1.8 °F) NTC: 0.7% span	Pt100, mV e mA: 0.2 % span T/C: 0.2% span ±1 °C	Pt100 / mV: 0.15 % span T/C: 0.15 % span ±1 °C NTC: 0.45% span
J, K, T, N, R, S, B, E, Pt100, Pt1000, NTC, and 0-50 mV	J, K, T, N, R, S, B, E, Pt100, and 0-50 mV	J, K, T, N, R, S, B, E, Pt100, Pt1000, NTC, and 0-50 mV	J, K, T, N, R, S, B, E, Pt100, Pt1000, NTC and 0-50 mV	J, K, T, N, R, S, B, E, Pt100, 0-50 mV, 0-10 V, 0-20 mA, and 4-20 mA	J, K, T, N, R, S, B, E, Pt100, Pt1000, NTC and 0-50 mV
4-20 mA 20-4 mA		4-20 mA	4-20 mA (20-4 mA) 0-10 V (10-0 V)	4-20 mA 20-4 mA	4-20 mA
See manual			See manual		
USB Micro-B Type	USB Mini Type	Through TxConfig-HRT interface or HART® certified handheld	USB Micro-B Type	TxConfig-USB interface	Through TxConfig-HRT interface or HART® certified handheld
TxConfig II	TxConfig	TxConfig II or HART® certified software	TxConfig II	TxConfig	TxConfig II or HART® certified software
-40 to 85 °C (-40 to 185 °F) 0 to 90% RH	-20 a 75 °C 0 a 90% RH	-40 to 85 °C (-40 to 185 °F) 0 to 90% RH	-40 to 85 °C (-40 to 185 °F) 0 to 90% RH		
Loop powered 4-20 mA (12 - 35 Vdc)		Loop powered 4-20 mA (8.5 - 36 Vdc)	Loop powered 4-20 mA (12 - 35 Vdc)		Loop powered 4-20 mA (8.5 - 36 Vdc)
34 mm x 18 mm (1.34 in x 0.71 in)	44 mm x 24 mm (1.73 in x 0.94 in)	43.5 mm x 20.5 mm (1.71 in x 0.79 in)	114 mm x 99.5 mm (4.49 in x 3.92 in)	77 mm x 72 mm (3.03 in x 2.83 in)	114 mm x 99.5 mm (4.49 in x 3.92 in)
ABS UL94-HB	ABS	ABS UL94-HB	ABS UL94-HB	-	ABS UL94-HB
Head			35 mm DIN rail		

Pressure Transmitters

Current Loop Indicator

LoopView is a two-wire 4-20 mA loop-powered indicator. Its excellent accuracy allows to indicate several variables like temperature, pressure, differential pressure, flow, pH, acceleration and others.

LoopView is powered by the current loop itself and it is meant to be inserted into sensors already installed in industrial facilities.

This device has a 4-digit display and 2 keys, which allow for quick and easy adjustment of indication range, decimal point position, digital signal filter and user calibration.

Parameter configuration is password protected and can be done directly via the front panel keys of the loop indicator.

- No extra power supply required
- DIN43650 standard sandwich assembly
- Legacy installation compatibility
- Push-button easy configuration



LoopView

Ultra Low Differential Pressure Transmitter

Ideal for **HVAC, clean-room and flow measurement** applications, the **NP785** is an ultra low differential pressure transmitter for measuring very small over-pressure, under-pressure and differential pressure in neutral, non-corrosive gaseous media. It provides a pressure proportional linear signal output with configurable measuring range via USB using the configuration software.

NP785 can operate bi-directionally, providing the ability to measure differential pressure ranges **from vacuum to positive pressure**. It is housed in a DIN rail mountable ABS/PC enclosure and its nickel plated brass fittings accept pneumatic hoses with 4 or 6 mm internal diameter.

The analog output can be set to either 0-10 V or 4-20 mA while having an RS485 port with Modbus RTU communication protocol. Designed for HVAC and industrial environment, the NP785 ensures temperature compensation for long-term stability and complies with EMC standards, providing robustness and reliability for a wide range of applications.

- Available nominal ranges: ± 50 Pa (± 0.2 inH₂O) to ± 1000 mbar (± 14.5 Psi)
- Ranges fully configurable by software within rated range
- Temperature compensated for higher stability at low pressures
- Output signal DC 0 to 10 V or 4 to 20 mA and slave Modbus RTU, in one-only-model
- Resistant to overpressure
- Auto-zero Key
- Diagnostic LED



NP785

Pressure Transmitters

The rangeability of **NP640** pressure transmitter brings versatility, allowing its transmission ranges to be turned down to up to 1/3 of its nominal range. Featuring high accuracy coupled with temperature stability, the **NP640** performs well in the most challenging applications and in harsh environments.

- Customer configuration of range via USB
- All stainless steel media compatibility
- High accuracy 0.25% of full scale
- USB Configuration via free software and adapter interface



NP640

Through the **TxConfig DIN43650** interface and the free **TxConfig II** software the **NP6xx** pressure transmitters series can be fully configured according to customer's preferred range and unit needs (bar, mbar, Mpa, kPa, kgf / m2, kgf / cm2, atm, mH2O, psi).

In addition, output status can be set up for upscale or downscale alarm in case of error and zeroing function is also available. The **TxConfig II** software brings great versatility to the end user by allowing range configuration right in the process.



Configuration via the TxConfig DIN43650 interface and the free TxConfig II software



	NP400	NP640
Pressure Sensor	Piezoresistive (ceramic)	Polysilicon piezoresistive (oil filled)
Software Configuration	-	TxConfig II (Via NOVUS Interface TxConfig DIN 43650 NOVUS)
Transmission Rangeability	-	3:1
Pressure Range (bar)	0...2, 5, 10, 16, 25, 40, 60, 100, 160, 250, 400	0...1, 4, 10, 16, 25, 40, 60, 100, 160, 250, 400
Pressure Range (psi)	0...30, 75, 150, 200, 400, 600, 900, 1500, 2000, 4000, 6000	0...15, 60, 150, 250, 375, 600, 900, 1500, 2000, 4000, 6000
Material in Contact with the Medium	Stainless steel 316 / FKM / ceramic (Al 203 96%) ₃	All stainless steel 316
Housing Material	Stainless steel 316	
Power Supply	11 ~ 33 Vdc	
Output Signal	4-20 mA	
Accuracy (Including Hysteresis, Linearity and Repeatability)	<60 bar ± 0.5 % FS >100 bar ± 1.0 % FS	± 0.25 % FS
Process Connection	¼ NPT , ½ NPT , ½ BSP , ¼ G	
Electrical Connection	DIN 43650 connector	
Operating Temperature	- 20 to 70 °C (-4 to 158 °F)	
Thermal Drift	< ± 0.06 % FS/°C	< ± 0.05 % FS/°C
Dynamic Response	< 30 ms	
Overpressure	2 x FS	

Controllers

PID Controller with LCD Display

N1050 is a PID temperature controller with LCD that combines high performance and vivid design. It combines the proven robustness of **NOVUS** PID algorithm with a large and bright easy-to-read dual color 11-segment LCD display with alphanumeric mnemonics and crystal clear status signaling.

It also features 5 ramp-and-soak profile programs, soft start output and timer function which complement the advanced features of the controller.

- Wide and high contrast dual color LCD display
- Distinguished multi angle viewing
- Compact depth, suitable for restricted spaces
- Elegant design for machines
- Ramp and Soak programs and timer function



N1050

Temperature PID Controllers



	N1030	N1030T	N1040	N1040T	N1020	N1050	N480D
Input Sensor	J, K, T and Pt100				J, K, T, R, S, E, N, Pt100 and 0-50mV	J, K, T, S and Pt100	J, K, T, R, S, E, N and Pt100
PID Control Features	Auto tune				Auto tune Self adaptive	Auto tune	Analog (optional) Auto tune
Control Action	Heating or cooling						Heating or cooling
Control Output	1 pulse Up to 2 relays		1 pulse Up to 3 relays Analog (optional)	1 pulse Up to 3 relays	1 pulse 1 relay	1 pulse Up to 3 relays Analog (optional)	
Ramp and Soak	-	-	-	-	1 ramp	5 programs 4 segments	1 program 9 segments
Special Functions	1 alarm (6 types)		Soft-start PID loop break detection 2 alarms (6 types)			2 alarms (7 types)	2 alarms (8 types)
Advanced Functions	-	Timer	-	Timer			-
Optional Resources	-	-	RS485 Modbus	-	RS485 Modbus		-
Bluetooth	-						
USB Configuration	-	-	Quicktune				Quicktune
Certification	CE, UL	CE, UL	CE, UL	CE, UL	CE, UL	CE, UL	CE, UL
Power Supply	100-240 Vac/dc or 12-24 Vdc (optional)						
Housing	48x48 DIN 1/16				48x24 DIN 1/32	48x48 DIN 1/16	48x48 DIN 1/16



Compact PID Controller









N1030 is a temperature controller that features a high performance PID algorithm in a **very compact housing** with **only 35 mm depth**.

Its innovative compact construction and the convenient **detachable connector** provide an easy set up on short profile panels, optimizing scarce space and reducing installation cost. It has two outputs always available which can be configured both as a control or an alarm.



- Compact profile, only 35 mm depth
- Detachable connector simplifies device installation, commissioning and maintenance
- IP 65 protection rate ensures resistance to water jets
- Protection and safety according to UL94 V-2 anti-flame housing
- Timer and two relay options to suit different processes

Process PID Controllers



								
	N960	N120	N1200	N1200 HC	N20K48	N2000	N2000 S	N3000
	J, K, T, R, S, E, N and Pt100	J, K, T, R, S, E, B, N, Pt100, 4-20mA, 0-50mV, 0-5V and 0-10V	J, K, T, R, S, E, B, N, Pt100, 4-20mA, 0-50mV, 0-5V and 0-10V		J, K, T, R, S, E, B, N, Pt100, 4-20mA, 0-50mV, 0-5V and 0-10V	J, K, T, R, S, E, B, N, Pt100, 4-20mA, 0-50mV and 0-5V	J, K, T, R, S, N, Pt100, 4-20mA, 0-50mV and 0-5V	J, K, T, R, S, E, B, N, Pt100, 4-20mA, 0-50mV and 0-5V
	Analog (optional) Auto-tuning	Auto-tuning	Auto-tuning Auto-adaptive		PWM & analogic Auto-tuning Auto-adaptive	Auto-tuning		Analog (optional) Auto-tuning
	Heating or cooling	Heating & cooling with overlap	Heating or cooling	Heating & cooling with overlap	Heating or cooling		Slave	Heating or cooling
	1 pulse 2 relays 1 analog	1 pulse 2 relays	1 pulse Up to 3 relays 1 analog		Up to 25 pulse* Up to 9 relays* Up to 8 analog*	1 pulse Up to 4 relays 1 analog		
	1 program 9 segments	20 programs 9 segments	20 programs 9 segments			7 programs 7 segments		
	2 alarms (8 types)	Soft-Start Bumpless Manual/auto PID loop break 2 alarms (7 types)	Soft-Start Bumpless Manual/auto PID loop break 4 Alarms (8 types)			Soft-Start Bumpless Manual/auto 4 alarms (7 types)	Soft-Start Bumpless Manual/auto 2 alarms (9 types)	Soft-Start Bumpless Manual/auto 4 alarms (7 types)
	-	Digital input	Digital Input Remote SP SP retransmission Square root		Digital Input* Remote SP* Square root	Digital input Remote SP SP retransmission Square root 24 Vdc output	Digital input Retransmission SP Square root 24 Vdc output	Digital input Remote SP SP retransmission Square root 24 Vdc output
	-	Data logger	RS485 Modbus Heater break 24 Vdc output + 2 I/O	RS485 Modbus 24 Vdc output + 2 I/O	RS485 Modbus*	RS485 Modbus		
	-	-	-	-	Yes	-	-	-
	Quicktune	Quicktune	Quicktune	Quicktune	Quicktune and Quicktune Mobile	Quicktune	-	Quicktune
	CE, UL	CE, UL	CE, UL	CE, UL	CE, Anatel and FCC	CE, UL	CE, UL	CE, UL
	100-240 Vac/dc or 12-24 Vdc (optional)	100-240 Vac/dc	100-240 Vac/dc or 12-24 Vdc (optional)					
	96x96 DIN 1/4	Open board Dual display	48x48 DIN 1/16	48x48 DIN 1/16	48x48 DIN 1/16	96x48 DIN 1/8	96x96 DIN 1/4	

*Using micromodules

Controllers

Modular Process Controller

- **Adaptable resources** by adding micromodules
- **Wireless** diagnostics and easy field maintenance
- **Lowest depth** controller in the market
- Smartphone and PC **friendly configuration**



Software Interface

Configuration Software to Controllers and Indicators

QuickTune is a free software tool to configure **NOVUS** controllers and indicators. With its clean interface, any user can friendly access and modify all device functions for proper configuration. Designed to easy and quick commissioning, it provides diagnosis and monitoring resources to field technicians. More than a software, **QuickTune** is a tool. Furthermore, **QuickTune** offers the main features to meet most users and profile needs in the industry.

- Friendly and Clean Interface
- Allows Quick Commissioning
- Provides Device Configuration Management
- Unified tool for Controllers and Indicators
- Graphic Ramp and Soak Assistant



QuickTune



BATCH CONFIGURATION

Certain applications require annoying tasks, which is to replicate the configuration of many devices. The batch configuration offers the appropriate environment to set plug-and-play device configuration in sequence.



GRAPHIC RAMP AND SOAK ASSISTANT

Temperature applications with complex profiles should be translated from process recipe requirements to ramp and soak parameters. The assistant tool provides a wide graphical perspective of the process with intuitive features such as sliders, drag-and-drop and clicks over the chart, transcribing all setting automatically to ramp and soak data table.

VIA USB AND BLUETOOTH




N1040

USB



N20K48

VIA RS485 (MODBUS RTU)



USB



RS485



N1500



N1500



N1200



N1050

Electronic Thermostats

Refrigeration Thermostat with Defrost

- Refrigeration control with automatic defrost
- Defrost by compressor stop, resistance heating or reverse cycle
- Programmable defrost cycle intervals
- Keeps indication during defrosting cycle
- Programmable delay on power-up to prevent simultaneous loads
- Control relay can directly switch compressor up to 1 hp

Models:


N321R: one output for compressor, accepts sensor type NTC, Pt100 or Pt1000 and optional voltage protection for compressor

N323R: three outputs (compressor, defrost and fan), monitors 2 NTC sensors (chamber and evaporator)

N323TR: similar to **N323R** plus real time clock for scheduling defrost events, with weekly timer,

Typical application:

Refrigeration cooling counters and air conditioning systems



Solar Heating Controller

- Ideal for solar panels applications
- Operates by the temperature difference between the solar collector and the storage tank
- Uses 2 NTC type sensors (included)
- Output control relay drives the water circulation pump
- Protection against pipeline overheating or freezing


Models:

N321S: one output for circulation pump

N322S: two outputs for circulation pump and waer heater booster

Typical application:

Thermal tank, pool heating, and boiler



Cooling/Heating Controller

- Control with alarm or multi-stage
- Direct drive of compressors or electric heaters
- Programmable delay on powerup to avoid simultaneous switching
- Low, high or differential alarm functions
- Sensor type: NTC, Pt100, Pt1000, and thermocouples J, K and T

Models:


N321: one relay output control

N322: two outputs (control and alarm or second control)

N323: three outputs (control and 2 alarms or 3 control stages)

Typical application:

Cold chambers, ovens, food industry, and commercial refrigerators





Controller with Timer


- Suitable for processes with cyclic operation requirement
- Timer for forced defrost cycle or stirring of liquids
- Accepts the following sensors: NTC, Pt100, Pt1000, and thermocouples J, K and T
- Programmable delay on powerup to avoid simultaneous switching
- Control relay can directly switch compressor up to 1 hp
- Optional: audible alert and voltage protection for compressor

Models:

N322T: two outputs (control and defrost or timer output)

Typical application:

Milk cooling and ice cream machines



Electronic Humidistat

- Environment control, displays temperature and humidity
- Configurable interval between temperature and humidity indication
- Control relay can directly switch compressor up to 1 hp
- Heating or cooling temperature control
- Humidification or dehumidification control
- Uses integrated RHT probe (sold separately)


Models:

N322RHT: two relay outputs (either control or alarm)

N323RHT: three relay outputs (control, alarm or timer function)

Typical application:

Climate chambers, textile processes, and environmental control



Egg Incubator Controller


- Control of humidity and temperature in the incubator (heating and humidification or refrigeration and dehumidification)
- Cycle timing control for egg rolling
- Configurable interval between temperature and humidity indication
- Uses integrated RHT probe (sold separately)

Models:

N323RHT (EI): three outputs (humidifier, heating and egg roll motor)

Typical application:

Egg incubators



Indicators

Panel Meters

N1540 is a high technology process indicator designed for the best performance and reliability in most demanding applications. Based on an advanced and rugged hardware platform, the **N1540** can be fully configured from the frontal keyboard or USB port. The exclusive USB interface allows, for example, to configure several devices with the same parameters in an easy way, saving time in the setup. Compact, the device has a 34 mm depth and can be easily installed in panels where space is restricted.

- Universal input: TCs J, K, T, E, N, R, S, B, Pt100, 0-50 mV, 0-5 V, 0-10 V, 0-20 mA, and 4-20 mA
- Sampling rate up to 50 samples per second
- Two relays SPST 1.5 A / 240 Vca
- Holds minimum and maximum values



N1540

Cost Effective

Advanced Features



	N1040i	N1540	N1500G	N1500	N1500 FT	N1500 LC
Indicator Type	Universal		Universal		Flow rate	Load cell
Input Type	Thermocouples, Pt100, voltage and current		Thermocouples, Pt100, voltage and current		4-20 mA, NPN, PNP, dry contact or magnetic signal	Voltage and current
Accuracy	J, K, T, E: 0.25% ± 1 °C (± 1.8 °F) N, R, S, B: 0.25% ± 3 °C (± 5.4 °F) Pt100: 0.20% Voltage/Current: 0.2%		J, K, T, E: 0.25% ± 1 °C (± 1.8 °F) N, R, S, B: 0.25% ± 3 °C (± 5.4 °F) Pt100: 0.20% Voltage/Current: 0.2%		4-20 mA: ±0.2% of span Pulse: ±30 ppm @25 °C (77 °F) Magnetic: ±0.1 % @25 °C (77 °F)	0.2 % span
Resolution	15 bits		>14 bits	17 bits	15 bits	17 bits
Programmable Range	-1999 to 9999	-2000 to 30000	-1999 to 9999	-31000 to 31000 0 to 60000 0 to 120000	Scale factor	-31000 to 31000 0 to 60000 0 to 120000
Sampling Rate	55 sps		5 sps	5 to 15 sps	-	15 sps
Alarms	2 setpoints 7 alarm types 2 relay outputs		2 setpoints 7 alarm types 4 timing modes 2 relay outputs	4 setpoints 7 alarm types 4 timing modes 2 (up to 4) relay outputs	2 (up to 4) setpoints 4 alarm types 4 timing modes 2 (up to 4) relay outputs	4 setpoints 7 alarm types 4 timing modes 2 (up to 4) relay outputs
Special Features	Optional 24 Vdc output	Hold maximum / minimum custom linearization 24 Vdc output	Hold maximum / minimum custom linearization Square root Digital Input retransmission 24 Vdc output		Hold maximum / minimum Custom linearization Square root Digital input Analog retransmission Pulse retransmission 24 Vdc output	Hold maximum / minimum Custom linearization Digital input retransmission 10 Vdc or 5 Vdc output
Communication Interface	USB (Mini-B type) Optional RS485 Modbus		Optional RS485 Modbus			
Certification	CE,UL		-		CE, UL	
Frontal Protection Rate	IP65		IP30		IP65	
Power Supply	100-240 Vac/dc or 12-24 Vdc		100-240 Vac/dc or 12-24 Vdc			
Housing	48x48 DIN 1/16	96x48 DIN 1/8	310 x 110 x 37 mm panel (12.20 x 4.33 x 1.46 in)		96x48 DIN 1/8	

Accessories

SSR - Solid State Relay

Increased lifetime, due to the fact that there are no moving parts, and thus, no mechanical wear. Internal protection circuit (Snubber) of the Output. **Zero cross switching**, which implies lower electrical noise. Silent operation. Control INPUT signal **optically isolated** from the OUTPUT. Suitable for replacing the contactor in AC installation.



Power Supply

The **NOVUS EDA Power Supplies** have **full range voltage input**, high efficiency, **DIN rail support** and operation temperature up to 70 °C. Attending **international standards and certifications** they are a robust solution to provide 24 Vdc for any industrial application.



Power Supply

The **FTR power supply** is a switching mode power supply to be connected directly to the line providing an isolated output. It is suitable for powering instruments such as 4-20 mA field transmitters.

The **FTR power supply** is designed to DIN rail mounting, inside electrical panel. Avoid excessive vibration, humidity, temperature and electromagnetic interference.



USB Port (Mini-B type) Panel Extension

USB port (Mini-B type) panel extension so that the USB is accessible on the panel. With a 30 cm extension, it makes the USB connection of the controller / indicator providing a mini-B type USB to fix on the panel with rubber-cap protection.



Vertical Energy

Switchgear Temperature Monitoring

NOVUS has launched **Telik Gardo**, a wireless remote temperature monitoring system for assets such as switchgear in power distribution systems. This solution enables online information for maintenance or loss management.

With wireless temperature sensors, **Telik Gardo** is simple and easy to install and deploy. It can be integrated with any SCADA system directly or any Cloud platform using an IoT Gateway, like the **AirGate 4G**.



Telik Gardo

Wireless Electrical Transformer Monitoring

NOVUS is launching the **Telik Trafo**, a wireless smart device capable of remote monitoring of current, voltage and temperature of distribution transformers. It provides assertive information for asset, energetic balance or loss management, checkinf transformer performance and load characteristics, allowing operation and maintenance teams to react on time.

Its wireless communication allows electricity companies to widespread monitoring.



Telik Trafo

Wireless Temperature Transformer Monitoring

NOVUS is launching the cost effective **Telik Trafo Lite**, a wireless device capable of remote monitoring of distribution transformers **temperature**. It checks continously the transformer body temperature, providing understanding of load characteristics and thus predicting any anomaly or degradation. This assertive information of the assets allows management to react on time, moving operation and maintenance teams to the field to the right location.

Telik Trafo Lite features **long-range communication**, **battery operation** and **5-year lifespan**.



Telik Trafo Lite

Metrology Laboratory



Choosing the right partner ensures your customer satisfaction

NOVUS Metrology Lab is ISO-17025 accredited by the Brazilian National Calibration Body, a signatory of the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Agreement (MRA). Its calibration certificates are recognized in over 70 countries, covering metrology services for temperature, relative humidity, pressure, electrical parameters, conductivity and pH instruments.

Customized services to meet our customer's expectations of deadline and application is what makes **NOVUS Metrology Laboratory** the right partner for your business bringing all the credibility that an accredited service with internationally recognized certificate can offer.



Economy

- Calibration at **NOVUS** facilities.
- You buy the device and the service with just one process.
- Avoid additional logistic costs.



Productivity

- Field calibration services (please check covered regions).
- Highly qualified professionals.
- The device is calibrated at the points and ranges you need.



Agility

- Devices calibrated from the factory.
- Customized and scheduled services.



Trustworthy

- High accuracy: significantly lower uncertainty values.
- ABNT NBR ISO/IEC 17025.

SCOPE OF ACCREDITATION




Temperature and Humidity



Electricity and Magnetism



Pressure





**We measure with accuracy.
We control with excellency.
We record with reliability.**

CANOAS - HEADQUARTER

Rua Engenheiro Homero Carlos Simon, 737
Guajuviras
92442-000 - Canoas - RS - Brazil
Phone: +55 51 3323-3600

USA

201 South Biscayne Blvd, Suite 1200
Miami, FL - 33131 - USA
Phone: +1 786 235-2674
info@novusautomation.com

SÃO PAULO

Rua Sampaio Viana, 75/12º andar
Paraíso
04004-911 - São Paulo - SP - Brazil
Phone: +55 11 3097-8466
sp@novusautomation.com

ARGENTINA

Zapiola, 829 C1426ATQ
Colegiales
Buenos Aires - Argentina
Phone: +54 11 4554-6441
argentina@novusautomation.com

CURITIBA

Rua Sete de Setembro, 4848 Cj.1302
Batel
80240-000 - Curitiba - PR - Brazil
Phone: +55 41 3244-0514
pr@novusautomation.com

FRANCE

26 chemin de la Madone, Bât D
Lentilly
Lyon - France
Phone: + 33 4 78 81 09 01
info@novusautomation.fr

Follow us on our social media



www.novusautomation.com

NOVUS

We Measure, We Control, We Record