

此 PDF 文档中显示的数据是由我们的在线目录生成的，仅供参考，请以实际产品说明书为准。

### **GS8272-EX.MR RTD/TC,RS485,Relay Isolated Barrier(1 channel)**

Temperature Input,relay,RS485 Output Isolated Barrier.transfer 4~20mA signal which linearly Transfer by thermal resistance or thermal couple in fidd from hazardous area to safe area isolatedly , at the same time,provide one channel of RS-485 bus output which based on MODBUS-RTU protaol and two channels of relay alarm output. input and output isolation.The product needs an independent power supply.



Number of channels: 1input/3outputs

Input signal: PT100 ,Cu50 ,Cu100 ,T ,E ,J ,K ,N ,R ,S ,B

RS-485 Output: Involve

Relay alarm output: Involve

Power Connection Mode: Bus Power Supply

## 产品参数

**上海辰竹仪表有限公司**

SHANGHAI CHENZHU INSTRUMENT CO.,LTD.

**如需更多信息，请与辰竹联系 For more information, please contact:**

销售服务 Sale service: 021-64360668

邮箱 Mail: [chenzhu@chenzhu-inst.com](mailto:chenzhu@chenzhu-inst.com)

技术支持 Tech service: 400 881 0780

网址 Web: [www.chenzhu-inst.com](http://www.chenzhu-inst.com)