

此 PDF 文档中显示的数据是由我们的在线目录生成的，仅供参考，请以实际产品说明书为准。



C-5T2-EX.M SPD for Signal (5V; 2 wires; In=10kA; Intrinsic Safety) 7059240

SPD for 5V signal; 2 wires; Intrinsic Safety; Thermocouple; RS-485; CAN; Ex ia IIC T6...T4 Ga; C2: 20kV/10kA/line; grounding via the rail directly



Voltage: 5V

wire: 2

Nominal discharge current In: 10kA

EX: Intrinsic safety

Connection: Push-in connection

产品参数

Product Features

Features	5V; 10kA; Intrinsic Safety; Two Wire
----------	--------------------------------------

Protections

Protected Objects/Systems	TC; RS-485; CAN
---------------------------	-----------------

Dimensions

Depth	54.5mm
Width	6.0mm

Height	82.0mm
--------	--------

Housing

Colors	Blue
Flame Retardant Grade	V0
Protection Level	IP20
Material	PA66
Brand	Dinkle

Basic Parameter

Response Time	1ns
Resistance per Wire	1.1ohm
Bandwidth	220kHz (-0.5dB)
Leakage Current	< 10uA
Maximun continuous operating voltage U_c	6VDC
Nominal operating voltage U_n	5VDC
Nominal Operating Current I_L	500mA

Security Data (Lightning Protection)

Voltage Protection Level Up (8/20us)	40V (Line to Line) /600V (Line to Ground)
Impulse Current I _{imp} (10/350us)	2.5kA
Maximum Discharge Current I _{max} (8/20us)	20kA
Nominal Discharge Current I _n (8/20us)	10kA

Security Data (Explosion-Proof)

Maximum Internal Inductance L _i	0mH
Maximum Internal Capacitance C _i	0μF
Maximum Input Power P _i	5.32W
Maximum Input Current I _i	500mA
Maximum Input Voltage U _i	6V

Safety Characteristic Parameter (SIL)

Safety Integrity Level (SIL)	SIL3
Safe Failure Fraction (SFF)	90.75%
λ _{DD}	1.68E-08

λ DU	1.71E-09
λ SD	0.00E+00
λ SU	5.37E-08

Product Approvals

Certification	Explosion-Proof Certification;Lightning Protection Certification;Functional Safety Certification; CE Certification
---------------	--

Certification

Explosion-Proof Certification	Ex ia IIC T6...T4 Ga
Lightning Protection Certification	Shanghai Lightning Protection Products Test Center
Functional Safety	SIL3

Ambient Requirements

Maximum Altitude	2000m
Applicable Location	Cabinet、Explosion-Proof Tank
Permissible Humidity (Operation)	10%—90%
Ambient Temperature (Storage)	-40—85°C
Ambient Temperature	T4:-40~+80°C T5:-40~+70°C T6:-40~+50°C

(Operation)	
-------------	--

Connection Parameters

Connection Method	Terminal Connection
Stripping Length	8mm
Conductor Cross Section Flexible	0.2—1.5mm ²
Conductor Cross Section Solid	0.2—1.5mm ²

Mounting

Mounting Method	35mm Lead Rail
Interface	Push-in
Mounting Position	Cabinet

上海辰竹仪表有限公司
SHANGHAI CHENZHU INSTRUMENT CO.,LTD.

如需更多信息，请与辰竹联系 For more information, please contact:

销售服务 Sale service: 021-64360668

邮箱 Mail: chenzhu@chenzhu-inst.com

技术支持 Tech service: 400 881 0780

网址 Web: www.chenzhu-inst.com